Single SMS Sending

Request URL

```
https://{domain}/sms/send?spid=xx&pwd=xx&das=xx&timestamp=xx&sm=x
```

Request Method

GET

Parameter Description

Field	Type	Name	Description
spid	string	Interface account	
pwd	string	Encrypted password	**Important note 3**
das	string	Phone number	Must include international code, e.g., 0062
sm	string	Message content	Must be converted to hexadecimal (character length is based on original text)
timestamp	string	Current Unix timestamp (seconds)	Example: 1601028870
senderid	string	Optional	Field enabled for partners

Response

```
{
  "code": 0,
  "msg": "Success",
  "data": {
    "msgid": "100123",
    "parts": 1  //Current SMS calculated number of segments
  }
}
```

Status Code (code) Description

- 0 -- Submission successful
- 101 -- Required fields cannot be empty (note request method is GET)
- 102 -- Verification failed (Unix timestamp is time zone independent, ensure error range [-10s, 10s])
- 103 -- spid does not exist
- 104 -- Password does not match (parameter must include timestamp)
- 105 -- No available channel (please contact administrator to confirm channel configuration)
- 106 -- Configuration error
- 107 -- Phone number is blacklisted
- 108 -- Content exceeds maximum character count
- 109 -- Parsing failed, please confirm interface parameters
- 110 -- Request IP restricted
- 111 -- Phone number sending restricted (too many attempts)
- 120 -- System error, please try again later (**Important note 1.1**)

□□□ #1
□ Admin □□□ 4 □□□ 2025 08:55:25
□ Admin □□□ 4 □□□ 2025 08:55:40