Clear the Token interface

Description

Note: When there is a new extension or an abnormality occurs after the extension is adjusted, you can clear the Token through this interface, and then obtain the Token again to continue the operation.

Request method: POST, form-data format

request parameters

parameter name	type	Is it necessary	illustrate
service	string	yes	App.Sip_Auth.Logout
token	string	yes	Token string

Interface request example PHP

```
<?php
    $apiUrl = 'http://127.0.0.1:8080';
    $postFields = [
        'service'   => ' App.Sip_Auth.Logout',
        'token'     => 'ABCDEFG',
    ];
    $curl = curl_init();
    curl_setopt($curl, CURLOPT_URL, $apiUrl);
    curl_setopt($curl, CURLOPT_POST, 1);
    curl_setopt($curl, CURLOPT_POSTFIELDS, $postFields);
    curl_setopt($curl, CURLOPT_RETURNTRANSFER, 1);
    $response = curl_exec($curl);
    $curlError = curl_error($curl);
    curl_close($curl);
    var_dump($response);
?>
```

return data structure example

```
{
    "ret": 200,
    "data": {
        "status": 0,
        "desc": "logout successful",
        "reqtime": 1602655204,
        "rsptime": 1602655204
    },
    "msg": ""
}
```

□□□ #1

□ Admin □□□ 4 □□□ 2025 10:07:05

□ Admin □□□ 4 □□□ 2025 10:07:24