Common API - Obtain authorization token interface

Interface Description

Tokens required to access other interfaces must be obtained from this interface through the authorized Appid and Accesskey (except for the batch IVR interface). The timeliness of the interface authorization Token is 12 hours.

Request method

POST, form-data format

request parameters

parameter name	type	Is it necessary	illustrate
appid	string	yes	authorized appid
accesskey	string	yes	authorized accesskey
service	string	yes	App.Sip_Auth.Login

Interface request example?PHP?

```
<?php
    $apiUrl = 'http://127.0.0.1:8080';
    $postFields = [
    'service'    => 'App.Sip_Auth.Login',
    'appid'      => 'ABCDEFG',
    'accesskey'  => 'ABCDEFG',
    ];
    $curl = curl_init();
    curl_setopt($curl, CURLOPT_URL, $apiUrl);
    curl_setopt($curl, CURLOPT_POST, 1);
    curl_setopt($curl, CURLOPT_POSTFIELDS, $postFields);
    curl_setopt($curl, CURLOPT_RETURNTRANSFER, 1);
    $response = curl_exec($curl);
    $curlError = curl_error($curl);
    curl_close($curl);
```

```
    var_dump($response);
?>
```

Return Data Structure Example

```
{
    "ret":200,
    "data":{
        "status":0,
        "desc":"Authorization successful",
        "result":{
            "companycode":"1",
            "companyname":"test",
            "token":"773a70dd02f0695d50205e9b267692b9",
            "authtime":"2020-01-01 00:00:00",
            "authmodel":""
        },
        "reqtime":1581240882,
        "rsptime":1581240882
    },
    "msg":""
}
```

Return parameter description

parameter name	type	illustrate
companycode	int	Company code
companyname	string	Company Name
token	string	Authorization token, used to access other interfaces

Revision #2
Created 4 December 2025 07:27:25 by Admin
Updated 4 December 2025 07:28:33 by Admin