# Predictive Outbound - Set the pre-test outbound task status interface

## Interface Description

Set the status of the pretest outbound task

## request parameters

| parameter name | type | Is it necessary | illustrate |
| --- | --- | --- | --- |
| service | string | yes | App.Sip_Yccall.TaskSet |
| token | string | yes | The token obtained through the authorization interface |
| taskid | string | yes | The unique id returned when the task was created |
| taskstatus | int | yes | Set task status 1: open, 2: pause, 3: end |

## Interface request example?PHP?

```
<?php
    $apiUrl = 'http://127.0.0.1:8080';
    $postFields = [
        'service'   => 'App.Sip_Yccall.TaskSet',
        'token'     => 'ABCDEFG',
        'taskid'    => 'ABCDEFG',
        'taskstatus' => 1,
    ];
    $curl = curl_init();
    curl_setopt($curl, CURLOPT_URL, $apiUrl);
    curl_setopt($curl, CURLOPT_POST, 1);
```

```
    curl_setopt($curl, CURLOPT_POSTFIELDS, $postFields);
    curl_setopt($curl, CURLOPT_RETURNTRANSFER, 1);
    $response = curl_exec($curl);
    $curlError = curl_error($curl);
    curl_close($curl);
    var_dump($response);
?>
```

# return data structure example

```
{
    "ret": 200,
    "data": {
        "status": 0,
        "desc": "successfully set",
        "reqtime": 1581496800,
        "rsptime": 1581496800
    },
    "msg": ""
}
```

# Return parameter description

| parameter name | type | illustrate |
| --- | --- | --- |
| desc | string | return description |

Revision #1
Created 4 December 2025 07:41:32 by Admin
Updated 4 December 2025 07:42:03 by Admin