Voice Call API - Make a voice call

Interface Description

Initiate a call directly to a number, most of which are applicable to calling the interface after clicking "Call" on the web page.

Request method

POST, form-data format

request parameters

parameter name	type	Is it necessary	illustrate
service	string	□	App.Sip_Call.MakeCall
token	string	□	The token obtained through the authorization interface
extnumber	string	□	Ext
destnumber	string	□	target number
disnumber	string	□	Caller ID, if left blank, a random caller ID will be selected
userid	string	□	Custom parameters (employee id)
chengshudu	string	□	Custom parameters (maturity)
memberid	string	□	Custom parameters (member id)
customuuid	string	□	Custom parameters (customer id)

Interface request example?PHP?

```
<?php
    $apiUrl = 'http://127.0.0.1:8080';
    $postFields = [
        'service'   => 'App.Sip_Call.MakeCall',
```

```
        'token'     => 'ABCDEFG',
        'extnumber'  => 'abcdefg',
        'destnumber'  => 'abcdefg',
        'disnumber'  => 'abcdefg',
        'userid'  => 'abcdefg',
        'chengshudu'  => 'abcdefg',
        'memberid'  => 'abcdefg',
        'customuuid'  => 'abcdefg',
    ];
    $curl = curl_init();
    curl_setopt($curl, CURLOPT_URL, $apiUrl);
    curl_setopt($curl, CURLOPT_POST, 1);
    curl_setopt($curl, CURLOPT_POSTFIELDS, $postFields);
    curl_setopt($curl, CURLOPT_RETURNTRANSFER, 1);
    $response = curl_exec($curl);
    $curlError = curl_error($curl);
    curl_close($curl);
    var_dump($response);
?>
```

return data structure example

```
{
    "ret": 200,
    "data": {
        "status": 0,
        "desc": "Call command sent successfully",
        "reqtime": 1581389402,
        "rsptime": 1581389402
    },
    "msg": ""
}
```

Revisión #1
Creado 4 diciembre 2025 08:21:10 por Admin
Actualizado 4 diciembre 2025 08:21:39 por Admin